

SS Cherry Wax



Technical Data Sheet (11/15/16)

HIGH SHEEN CHERRY SCENTED WATER BASED ACRYLIC FLOOR WAX

PRODUCT DESCRIPTION

SS Cherry Wax is a cherry scented water based acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. SS Cherry Wax yields rapid gloss build along with long-term wear characteristics. It's resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. SS Cherry Wax should be used on any sealed surface where a rapid high gloss sheen build and superior maintenance properties are desired.

BENEFITS AND FEATURES

- Non-flammable, non-combustible, non-corrosive. Not hazardous!
- Great smelling cherry scent is very pleasing to the nose.
- This formula contains only environmentally safe materials.
- High solids provides quality high sheen and resistance to abrasion and scuffing.

RECOMMENDED APPLICATIONS

SS Cherry Wax is recommended for interior sealed applications where a high sheen polish is desired.

TECHNICAL INFORMATION

Solids	21%	Dry Appearance	Crystal Clear
Drying Time*	1–2 hours	VOC Content	None
Re-Coat Time	1–3 hours	Blush Resistance	Excellent
Foot Traffic	12–24 hours	Solvent Resistance	Good
Wheel Traffic	24–48 hours	Concrete Adhesion	Superior (over sealed surfaces)
Application	40°F-85°F		
Wet Appearance	Milky White		

**Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.*

SPECIFICATIONS/COMPLIANCES

SS Cherry Wax is VOC and OTC compliant in all areas of the United States and many foreign nations.

APPROXIMATE COVERAGE RATES

Application Surface	First Coat	Optional Second Coat
Interior Sealed Surfaces	1000+ ft ²	1000+ ft ²

Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

INSTRUCTION FOR USE

SURFACE PREPARATION: Be sure the area of the concrete to be waxed is free of trash and debris. Protect all other areas. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If spray buffing, use a plastic or coated cardboard as a spray shield.

APPLICATION: Do not apply by pouring directly onto surface. Use a plastic roller pan. Apply by synthetic fiber wax applicator, lambs wool applicator, or clean sponge mop.

Apply at a rate of 1000+ square feet per gallon in very thin coats only. Apply in one direction to a consistent, even, and uniform finish. If puddling or pinholes appear, work them out into a thin coat.

Allow to dry 1–2 hours. Repeat process as many times as necessary to achieve required gloss sheen build. If spray buffing, dilute wax 1:2 with water. Apply using a fine to medium mist sprayer over a small area at a time. Buff that area until the liquid has disappeared and a superior shine is left.

Periodic maintenance coats may be necessary as traffic will eventually dull the surface. Simply mop the area clean using a light detergent solution. Allow to dry and then apply a coat of SS Cherry Wax to rejuvenate the superior gloss sheen. When periodic maintenance of SS Cherry Wax is used, it will help protect the coating/sealer. Regular dry mopping will also extend the life of the floor system by removing abrasive materials that otherwise act as aggressive sandpaper.

CLEAN UP

Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Product may be re-coated up to 100 times. When product removal is necessary, use a light ammonia and water solution to strip the waxed area back to the sealed surface.

SHELF LIFE

SS Cherry Wax has a shelf life of one-two year in it's original, sealed, unopened container.

PACKAGING

SS Cherry Wax is packaged and stocked in 1 gallon jugs and 5 gallon pails. 55 gallon drums are available on special order.

PRECAUTIONS AND LIMITATIONS

- SS Cherry Wax will freeze. It is recommended to store in an area between 50°F and 85°F.
- Do not puddle or apply in thick coats. SS Cherry Wax should be applied in several very thin coats.
- SS Cherry Wax is harmful if swallowed. Abide by recommended safety guidelines.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- SS Cherry Wax was designed for interior use only. It is not recommended for exterior use.
- SS Cherry Wax should only be diluted for spray buffing only. Do not dilute for normal use unless necessary.
- SS Cherry Wax should only be used as a sacrificial coating and not used as a sealing compound.
- The statements made within this technical data sheet, SDS, product labels, etc are guidelines only. The end user should always perform tests and product evaluations prior to application to ensure suitability for particular uses.

SPECIAL NOTES

Please consult Safety Data Sheet (SDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.

WARRANTY:

SS Specialties and its affiliates warrant our products to be of good quality, free of defects and will conform to our published specification in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, SS Specialties will replace defective materials ninety days after SS Specialties has shipped the product. All our warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will SS Specialties be liable for any consequential damages in excess of the purchase price of the product.



www.ssspecialtiesconcrete.com

Distributed by SS Specialties | 121 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-525-3367