

SS Supreme Color Pac



Technical Data Sheet (07/24/12)

SOLVENT BASED TINT PACK FOR ACRYLIC SEALERS

PRODUCT DESCRIPTION

SS Supreme Color Pac is a high solids, concentrated, solvent based acrylic tint system specially formulated for solvent based acrylic sealers. SS Supreme Color Pac is formulated with high quality, ultra fine particle pigments designed to quickly disperse in solvent based acrylic sealers. SS Supreme Color Pac is a superior choice to obtain a semi transparent stain or a solid opaque colored finish in most solvent based acrylic sealer systems.

BENEFITS AND FEATURES

- 12 popular colors.
- Very economical and decorative way to seal a variety of concrete substrates.
- Reduces the inventory space and cost.
- Fast and efficient method of staining, as opposed to multiple steps of other stain systems.
- May be mixed to be translucent or opaque.

RECOMMENDED APPLICATIONS

SS Supreme Color Pac is recommended for use on unsealed or untreated warehouse floors, garages, basements, docks, driveways, side-walks, pool decks and any other concrete surface to create a solid or semi solid color appearance with the added benefits of sealing and dust proofing.

TECHNICAL INFORMATION

Solids [Diluted]	Depends on sealer used
Drying Time	1–2 hours
Re-Coat Time	4–24 hours
Foot Traffic	4–6 hours
Wheel Traffic	24–48 hours
Application Temp	40°F–85°F
Wet Appearance	Varies depending upon color
Dry Appearance	Varies, High Gloss
VOC Content	n/a
Blush Resistance	Good
Solvent Resistance	Minimal
Concrete Adhesion	Excellent

Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

APPROXIMATE COVERAGE RATES

FOR SEMI TRANSPARENT FINISH:

Approximate amounts added per 1 gallon: 2–8 ounces
Approximate amounts added per 5 gallon: 8–16 ounces

FOR SEMI OPAQUE FINISH STAIN:

Approximate amounts added per 1 gallon: 8 ounces
Approximate amounts added per 5 gallon: 32 ounces (1 quart)

Usage rates are suggested amounts only! Due to varying conditions of substrates, surface texture, porosity and desired appearance as well as sealer characteristics it is recommended to first test the suggested ratio to determine acceptability.

INSTRUCTION FOR USE

MIXING: Mix desired amount in a solvent based acrylic sealer for 1–2 minutes using a squirrel mixer prior to application. Allow any foam to settle prior to use. Material may separate during long term storage. Remix as needed.

Please note: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved. Be aware that less material will be applied and performance expectations may be limited.

Caution: Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmentation may cause color float or streaking. Especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application, the porosity of the surface, as well as the composition of the solvent based acrylic sealer.

Test SS Supreme Color Pac for compatibility with the solvent based acrylic sealer to be used prior to use.

CLEAN UP

Use Xylene. Dispose of containers in accordance with local and federal regulations.

SHELF LIFE

SS Supreme Color Pac has a shelf life of one year in its original, sealed, unopened container.

PACKAGING

SS Supreme Color Pac is packaged and stocked in quart jars only.

PRECAUTIONS AND LIMITATIONS

- SS Supreme Color Pac will not freeze. However, allow temperature to rise to 50°F prior to application.
- Recommend that all HVAC ventilation ducts be blocked or closed prior to application so solvents fumes are not distributed.
- Keep away from open flames. SS Supreme Color Pac is flammable and is very susceptible to ignition.
- Follow the application guidelines.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- SS Supreme Color Pac is designed for new or old concrete and to be applied in thin coats, rather than one thick coat.
- Please be aware that the finished product when cured may be slippery when wet. Use anti-skid additive as needed.
- SS Supreme Color Pac is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to substantially reduce the sealer to achieve translucence. Improper reduction may reduce durability.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.



www.ssspecialtiesconcrete.com

Distributed by SS Specialties | 121 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-525-3367

SSSupremeColorPac_Tech Data
07/24/12